

Seismic Support Vessel



SHIP DESIGN	SALT – Project 035
SHIP NAME	Ocean Fortune
CLASSIFICATION	Bureau Veritas
BUILDER	Cemre Marien Endustri Anonim Sirketi
PORT OF REGISTRY	Nassau
FLAG	Bahamas
MMSI	311 000 276
IMO NUMBER	9742431
CALL SIGN	C6BI9 (Charlie Six Bravo India Nine)

OWNER:	SUN ATLANTIC LTD	MANAGER:	VESTLAND MANAGEMENT AS N-5384 TORANGSVÅG
---------------	-------------------------	-----------------	---

MAIN DIMENSIONS

Length O.A	69,80 M
Length P.P	61,50 M
Breadth	17,00 M

CLASS NOTATIONS

I*HULL*MACH, SDS, *AUT-UMS, *CLEANSHIP BWT,
*AVM-DPS, *SYS-NEQ OSV
COMF-NOISE 3/COMF-VIB 3,
ICE CLASS 1B, Heavy Cargo 30,
MON-SHAFT, SPS 60, SDS, GREEN PASSPORT,
Unrestricted Navigation,
Special Service/Seismic Support Vessel

OUTLINE SPECIFICATION

MACHINERY AND PROPELLER PLANTS

Main Gen-sets:	4 x Yanmar 1000kw at 750 RPM
Emergency Generator:	1 x Scania 200 kW
Main Propulsion:	2 x Berg CPP in nozzles 2 x 1500 kW
FWD Azimuth Thruster:	1 x ZF 600 kW
Auxiliary boiler:	1 x Pyro 870 kW
Exhaust gas boiler	2 x Pyro for Heat Recovery from Engines
Heat Recovery System	1 x Pyro Complete Arrangement

DECK AND TANK CAPACITIES

All figures are approx.

Deck load capacity:	1000 Tons VCG 1m above deck
Deck Area approx.:	500 m ²
Tank volume for MDO:	500 m ³
Tank volume for HFO:	2000 m ³
Heating capacity HFO:	60 °C
Fresh water:	157.9m ³
Slop:	25 m ³
Grey water:	42.2 m ³
Bilge water holding tank:	26 m ³
Bilge water settling tank:	16 m ³
Sludge:	12 m ³
Waste oil:	8 m ³
FO drain:	5 m ³

GARBAGE DISPOSAL PLANTS

- 1 x Teamtec Incinerator 189 200 kcal/h (220kw)
- 1 x Bramidan Compactor, Marine B3 Denmark
- 1 x Food Waste Disposer IMC - 523

NAVIGATION

- 1 x Bridge Watch
- 1 x Furuno DS-80 Doppler Speed log with interface to conning
- 1 x Nortek Acoustic Doppler Current Profiler
- 2 x Furuno GPA 150 Dual DGPS
- 1 x Furuno FE-700 Echo Sounder interfaced to DGPS and conning
- 1 x Ratheon Anschuts Nautopilot 5300 with off-course recorder and alarm
- 2 x Ratheon Anschuts STD 22 Gyro Compasses
- 1 x Magnetic Compass Cassens & Plath ,REFLECTA/1
- 2 x Ratheon Anschuts Gyro Repeaters, forward and aft consoles
- 1 x Ratheon Anschuts Gyro Repeater in steering gear room
- 1 x Ratheon Anschuts Gyro Repeater on chart table
- 1 x Furuno X-Band IMO Chart Radar FCR-2829
- 1 x Furuno S-Band IMO Radar FAR-2837 S
- 1 x Furuno Radar slave display
- 3 x TECDIS 2138-A Telko Dual ECDIS
- 1 x SSAS
- 1 x Furuno VR-3000 VDR
- 2 x Alphantron Anemometers and Wind Sensors
- 1 x Kongsberg C-Joy (+ 1 remote control for port and stbd wings)
- 1 x Fuel Consumption "Econometer"
- 1 x Closed Circuit TV system (CCTV)
- 3 x monitors 17"
- 1 x CCTV recorder
- 13 x fixed cameras

LIFE SAVING EQUIPMENT

Ship Certificate:	60 persons
Life Rafts:	7 x 20 men RFD (3 on each side and one spare)
MOB:	1 x MARE SAFETY FRB 700 for max 15 pers
MOB Davit:	1 x Vestdavit PLH 4000 with shock absorber
Additionally Davit:	1 x Vestdavit PLR 12005 with shock absorber
Survival Suits:	Survival suits according to SOLAS for 60 persons
Rescue Frame:	Dacon net for picking up person in water

SPEED

Calm weather and sea conditions, draft 4,5 meters, auxiliary/hotel 200 KW
All figures shall be confirmed upon sea trial tests

Design theoretical speed:	13,4 knots
Bollard Pull (ex Azimuth)	51 tons
Fuel consumption 5 knots:	2,8 t/d
Fuel consumption 10 knots:	6,5 t/d
Fuel consumption 12 knots:	8,7 t/d
Fuel consumption 13 knots:	10,9 t/d

CARGO HANDLING EQUIPMENT

- 2 x Remote operated (deck and bridge) Bunkering Reels, NDM Norway
- 2 x 244m fuel-hoses 5"dia with "TODO" connections and "Weak Link"
- 1 x Remote operated (deck and bridge) dual-drum Reel, NDM Norway
- 1 x Bunkering operation towing line 170 m
- 1 x Emergency operation towing line 250 m
- 2 x Certified Fuel Oil Cargo Flow-meter connected to AIS
- 1 x Remote operated (deck and bridge) Streamer Reel with Spooler Capacity 8000 meters of 59 mm streamer, NDM Norway
- 1 x ABAS Offshore Crane 12 t @ 10 m outreach, 8 t @ 17 m outreach
- 2 x Rpm controlled HFO Cargo pumps with capacity 200m³/ 45m

- 1 x Remote operated (deck and bridge) Towing hook. SWL 70 t with Tension and Monitoring Control on bridge
- 1 x Pomek Dip Winch model DW-500

- Provision cargo rooms at 1st deck:
- 1 x Freezing room -22°C
- 1 x Refrigeration room for temperature + 4°C
- 1 x Dry provisions room +15°C

COMMUNICATION

- 1 x Furuno NX-700A Navtex
- 2 x Furuno TRON SART 20 Radar Transponder
- 1 x Furuno FA-150 AIS
- 1 x LRIT
- 2 x TRON 60S EPIRB manual
- 1 x Furuno RC-1800 T Radio Station, GMDSS A3
- 1 x Furuno FS-2575C MF/HF
- 2 x Furuno FM-8900S VHF on bridge
- 1 x Furuno FM-4721 VHF in ECR
- 3 x Jotron TRON TR-20 GMDSS VHF Portable
- 8 x Entel HT-833 UHF Portable with helmet equipment
- 2 x Entel HT-844 VHF Portable
- 4 x smoke diver helmet equipment
- 3 x Search lights on top of wheelhouse

Intercom also covering cargo and deck areas
PA System
Satellite Communication: Sailor , Felcom-500

Bridge	+47 23 96 11 77
Office	+47 23 96 11 78
Mobile phone	+47 90 17 53 96
E-mail	captain.fortune@vestlandoffshore.no

ACCOMMODATION

- Outfitted for 60 persons in spacious and comfortable facilities
- Client Cabins: 1 x two men
- Crew Cabins: 8 x single and 2 x two men
- Rest Cabins: for 46 persons
- Hospital: 1 x Highest offshore standard
- Office: 1 x fully outfitted
- TV Lounge: 1 x Comfortable outfitted for 12 persons
- Mess Room: 1 x outfitted for 40 persons
- Gymnasium: 1 x fully outfitted
- Entertainment: In Common Areas and all cabins on deck B
- Antiroll Tank: Yes, aft below bridge